

FICHE TECHNIQUE

Vêtements de protection

AluSkin



KOSTO
BUILT STRONG • BÂTI SOLIDE

Repair Kit for Aluskin Fabric

ALU-REPAIR-OR

Orange

ALU-REPAIR-NV

Navy

The kit makes repairs simple and easy, thanks to adhesive, durable and washable fabric parts. Iron-on parts offer great adhesion and are ideal for repairing damaged garments, holes and tears on the Aluskin range of garments.

The fabric of AluSkin garments offers an optimal protection for workers exposed to molten metals such as foundry workers and welders by protecting them from molten splinters, flames and heat and provides category 2 protection for workers at risk from electric arcs. The comfortable, lightweight fabric blend and the fit of the garment make AluSkin the ideal protective garment.

Fabric

- 54% FR Viscose / 20% Polyamide / 20% Wool / 5% Aramid / 1% Antistatic 330 gsm (9.73 oz/yd2)

Contents

2* 4" x 4"

2* 2" x 2"

Certifications

This fabric is certified with **NFPA 70E / ASTM F1506 -19a**



ALU-REPAIR-OR



ALU-REPAIR-NV

3 Easy Steps

CUT

PEEL

STICK



SPECIFICATION SHEET

Protective Clothing

AluSkin



KOSTO
BUILT STRONG • BÂTI SOLIDE

Related Items

VHKAD6
Ladies Aluskin
Shirt



VHKA01-VPKA31/33/36
Aluskin shirt and pants



VCKA01
Aluskin
Coverall CSA



Care Guide

Care Instructions

- Protective garments should be cleaned regularly, as per recommended instructions.
- Wash all garments after fixing all closure systems.
- Strictly wash garments inside out.
- Always wash your Flame Retardant PPE separately to avoid some migration of flammable loose fibers or components.
- Please make sure that garments are properly rinsed after wash.
- Do not dry in direct sunlight as this may cause color to fade.
- After cleaning the garment, please inspect before re-use




Wash care instructions

- Wash in 60°C, do not use detergents containing soap & chlorine.
- Do not bleach, or use acids when rinsing.
- Iron at low setting (below 110°C).
- Use dry cleaning agent other than Trichloroethylene.
- Tumble dry allowed.

Size chart

ALU-REPAIR-



REPAIR KIT				
			2"	4"
Width	1	po/in	2	4
	1	cm	5	10
Height	2	po/in	2	4
	2	cm	5	10