

Multi-Purpose Anchorage Connectors

These lightweight, portable anchors are a great choice for a variety of applications. Many are “choker” style, designed to create an easy-to-use anchor on an overhead location beyond normal reach—all with a high strength 22 kN (5,000 lb) rating.

Web Tie-Off Adaptor 5900578

Pass-through design makes attaching to anchorage quick and easy. 4.4 cm (1-3/4 in) polyester strength member with 7.6 cm (3 in). wide polyester wear pad x 1.8 m (6 ft).

5900578 Web tie-off adaptor x 1.8 m (6 ft)

5900577 Web tie-off adaptor x 0.9 m (3 ft) with web loop and D-ring pass-thru



Cable Anchorage Extension AJ408CG-6

Lightweight and extremely durable 6.4 mm (1/4 in) coated galvanized cable stands up to harsh environments. Snap hook at one end, O-ring at other x. 1.8 m (6 ft).

AJ47406-6 Cable tie off adaptor with two O-rings

Cable Dual Ring Tie-Off Adaptor 2190102C

6.4 mm galvanized cable dual-ring tie-off adaptor, carabiner at one end, two D-rings at the other x 1.8 m (6 ft).

2190100C 0.9 m (3 ft) Adaptor

2190101C 1.2 m (4 ft) Adaptor

2190110C 0.9 m (3 ft) Adaptor with Flemish eye termination

2190111C 1.2 m (4 ft) Adaptor Flemish eye termination

2190112C 1.8 m (6 ft) Adaptor Flemish eye termination



Carabiner 2000112

Reduced weight. Easy operation. Steel carabiners make for a versatile option to help keep your system securely connected. The 22 kN (5,000 lb) minimum breaking strength and 16 kN (3,600 lb) self-closing/locking gate enhance safety. 17.5 mm (11/16 in) opening.

2000117 With roll pin, 1.75 cm (11/16 in) opening

2000114 With 5.56 cm (2-3/16 in) opening

