

SPECIFICATIONS SHEET

Fall protection



KOSTO
BUILT STRONG • BÂTI SOLIDE

General Harness XPRO - 1 Ring, Class A

CHK201

This 5-point adjustable general harness gives you added comfort when working at height with the removable cushion padding in the shoulders. Class A, it is ideal for several types of work. Heavy-duty quick-connect buckles allow the harness to be put on and taken off quickly and the weight to be redistributed evenly.

Certification

- **CSA Z259.10 class A** certified
- **ANSI Z359.1**

Material

100% polyester for increased resistance to chemicals

Size:

Universal

Capacity

160kg (352lbs)

Removable legs, hips and shoulders padding for comfort.

Galvanized steel back D-ring

X in PVC to prevent tangling

Labels protector cover

Impact indicator

1 3/4" strap with a minimum of 2,722kg (6,000lb) breaking point with silver high-visibility tapes.

Seat strap

Chest buckle

5 adjustment points (2x legs, 2x body, 1x chest)

Adjustment with quick-connect buckles



SPECIFICATIONS SHEET

Fall Protection



KOSTO
BUILT STRONG • BÂTI SOLIDE

Associate Products

Harness **CHK210**

Harness **CHK214**



Connecting elements

Lanyards CCK



Self-Retracting Lifeline CDK



D-ring Extension
CCK008/CCK018



Tool Lanyard
CAK050



Anti-Trauma
Safety Strap
CSK001



Carrying Bag
K-BAG



Maintenance and Inspection

Maintenance

Clean after each use to maintain safety and durability.
Remove any dust, corrosive material or contaminants.
If the fall protection system cannot be cleaned with clean water, use mild soap and water, then rinse and wipe dry.
NEVER clean the fall protection system with corrosive materials.

Inspection

Before EVERY use, inspect the fall protection system for defects.

IMMEDIATELY remove the fall protection system from service if any defects or damage are found, or if it is exposed to fall arrest forces.

At least every 12 months, a competent person other than the user should inspect the harness.

Sizing Chart

