



Technical Datasheet

RPB® C40™ Climate Control Device

DESCRIPTION

The C40 Climate Control Device is a belt mounted air regulator and temperature control unit for RPB's supplied air respirator range.

The unit allows the user to cool incoming air by up to 52°F (29°C) or heat it by up to 33°F (18°C) and increase or decrease the flow of air coming into the respirator, increasing comfort, productivity and safety. It also features a swivel air inlet fitting.

Type description

Supplied air regulator and climate control device.

Packages available for NIOSH markets

	Part #
C40 with RPB Quick Connect Swivel Fitting	03-501
C40 with Schrader Twist Connect Swivel Fitting	03-504
C40 with RPB RZ Quick Connect Swivel Fitting	03-501-RZ

Packages available for CE & AS/NZS markets

	Part #
C40 with CEJN 342 Double Action Safety Fitting	03-502

Required components

- Approved RPB respirator head-top assembly
- Breathing tube
- Breathing airline

Approved respirators

NIOSH markets	Astro™, Nova 2000®, Nova 3®, T-Link®, Z-Link®, Z3®, Z4®
CE & AS/NZS markets	Nova 1®, Nova 3®, T-Link®, Z-Link®, Z4®



03-501 RPB C40 Climate Control Device

APPROVALS & STANDARDS

ISO9001
CERTIFIED COMPANY

NIOSH
National Institute for
Occupational Safety and Health
Only in conjunction with approved respirator.

CE 2797

EN14594:2005 3B
RESPIRATORY PROTECTION
Only in conjunction with approved respirator.

Protecting you for life's best moments.





Technical Datasheet

RPB® C40™ Climate Control Device (continued)

SPECIFICATIONS

Flow rate and airline requirements into the C40

- 18-25 cfm (510-708 lts/min)
- RPB certified 3/8" (9.5mm) internal diameter breathing airline.
- 55-100psi (depending on airline type).

Refer to instruction manual for detailed information.

Fittings and couplers

NIOSH	RPB® Quick Connect Swivel
	Schrader Twist Connect Swivel
	RPB® RZ Quick Connect Swivel
CE & AS/NZS	CEJN 342 Double Action Safety Swivel

Materials

Nylon	Injection molded parts
Polypropylene	Belt
Zinc Plated Steel	Fittings
Brass	Silencers
Nomex®	Optional FR belt
Acetyl	Buckles on FR belt

Operating temperature

14°F to 140°F / -10°C to 60°C

Storage temperature

14°F to 113°F / -10°C to 45°C <90%RH

Dimensions

2.85 x 7.8 x 2.5 in / 72.4 x 198.5 x 62.3mm (W x H x D)

Weight

C40 without belt	9.8oz / 277g
------------------	--------------

Warranty

1 year. Conditions apply, visit [rpbsafety.com/legal](https://www.rpbsafety.com/legal) for full details.



Employers

Read the C40 Climate Control Device and the respirator head-top instruction manuals and carry out the employer responsibilities.

Provide the manuals to all users.

Product users

Read the C40 Climate Control Device and the respirator head-top instruction manuals and follow the product user safety instructions.

Manuals are regularly updated.

Current version of manual and for other languages:

[rpbsafety.com/resources](https://www.rpbsafety.com/resources)

Contact

RPB Safety - Global Headquarters
2807 Samoset Rd, Royal Oak, MI 48073, USA

T: 1-866-494-4599

E-mail: sales@rpbsafety.com

www.rpbsafety.com

Protecting you for life's best moments.

