

SPECIFICATION SHEET

Protective Clothing



KOSTO
BUILT STRONG • BÂTI SOLIDE

Dazzle Arc and Welder Protection Coverall with 4" Reflective Tape and Zipper Leg Opening

VCKF10 / VCKF10T

This flame retardant intrinsic cotton fabric coverall is designed to protect workers exposed to welding sparks and category 2 electric arcs. The cinched waist with an elastic on the sides and the pleats on the back allow for better ease of movement. The coverall features numerous pockets for gear and a two-way front zipper with flap.

Certifications

- This garment is certified with **EN ISO 11611 (Class 1 - A1+A2)** for protection against welding projections
- **ATPV 14 cal/cm² (Cat. 2)** for arc flashes and flame resistant clothing
- **EN11612 (A1 A2 B1 C1 E3 F1)** for the resistance to heat and flame
- Antistatic **EN1149-5**
- Comply with **CSA Z96-22** for tape position
- **Class 3, Level 2** (orange coverall)

Fabric

- Intrinsic FR flame retardant fiber
- 99% cotton / 1% Antistatic
- 350gsm (10.32OZ/YD²)
- 4" reflective strips

Size:

Regular: 36 to 62

Tall: 38T to 62T



SPECIFICATION SHEET

Protective Clothing



KOSTO
BUILT STRONG • BÂTI SOLIDE

Related Items

VCK252 /VCK246
Polycoton Coverall



VCKF01
ArcFlash Coverall
ATPV 9.2cal/cm2




VCKA01
Aluskin Coverall



Care Guide

Care Instructions

- Protective garments should be cleaned regularly, as per recommended instructions.
- Wash all garments after fixing all closure systems.
- Strictly wash garments inside out.
- Always wash your Flame Retardant PPE separately to avoid some migration of flammable loose fibers or components.
- Please make sure that garments are properly rinsed after wash.
- Do not dry in direct sunlight as this may cause color to fade.
- After cleaning the garment, please inspect before re-use




Wash care instructions

- Wash in hot water; do not use detergents containing soap or chlorine.
- Do not bleach, do not use acids when rinsing.
- Iron at low setting (below 110°C).
- Use dry cleaning agent other than Trichloroethylene.
- Tumble dry allowed.

Size Chart

VCKF05-06



COVER ALL																	
			34	36	38	40	42	44	46	48	50	52	54	56	58	60	62
Poitrine	① po / in		43	44	45	46	47	48	49	50	51	52	53	54	55	56	57
	① cm		109	112	114	117	119	122	124	127	130	132	135	137	140	142	145
Longueur fourche	② po / in		34.5	35	35.5	36 1/4	37	37 3/4	38 1/2	39 1/4	40	40.5	41	41.5	42	42.5	43
	② cm		88	89	90	92	94	96	98	100	102	103	104	105	107	108	109
Jambe	③ po / in		30	30	30	30	30	30	30	30	30	30	30	30	30	30	30
	③ cm		76	76	76	76	76	76	76	76	76	76	76	76	76	76	76

* Measurements are based on finished garment. * For optimal fit it is recommended to try before purchase

PROTECTION • RELIABILITY • VALUE